

SMC1065N/SMC1065P Specifications:

Model	SMC1065N	SMC1065P
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734kHz	15.652kHz
Scanning Frequency(V)	59.94Hz	50Hz
Image Sensor	1/4" IT CCD	
Sync. System	Internal/Line-Lock	
Total Pixels Number	811(H) x 508(V) 410K	795(H) x 596(V) 470K
Effective Pixels Number	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	500 TV Line(Color), 570 TV Line(B/W)	
Video Output Level	1.0Vp-p (75Ω, composite)	
S/N Ratio	50dB (AGC off, Weight On)	
Min. Illumination	Color: 0.7Lux@F1.8, 0.005Lux(Sens-up), B/W: 0.02Lux@F1.8	
Day & Night System	Electronic sensitivity-up (DSS), ICR (AGC type)	
White Balance	Auto/Manual(Red, Blue Gain Adjustable)	
OSD Menu	On/Off	
Privacy Zone	ON/OFF (8 zone settings)	
Electronic Shutter Speed	1/60sec ~ 1/120,000 sec	1/50sec ~ 1/120,000 sec
Preset	127 positions with labels	
Swing	8 swings (Speed Selectable : 1°/sec ~ 180°/sec)	
Pattern	4 patterns (about 5min/pattern)	

Group	8 groups (max. 20 entries)
Panning/Tilting Range	Pan: 360° endless rotation; Tilt: 90°
Panning/Tilting Speed	Manual: 1° ~ 360°/sec; Preset: 360°/sec; Swing: 1°~180°/sec
Power Voltage	24VAC
Power Consumption	Max. 3.5W
Weight (Net)	Approx. 805.5g (without optional accessories)